

FieldSmart® Fiber Delivery Point (FDP)

Outdoor 24-Port Wall Box



Application

The FieldSmart FDP 24 Port Outdoor Wall Box is ideal for both residential MDUs and business-class environments. Configurable for either patch only, patch and splice (Clearfield's in-cassette splicing solution) or MPO plug-and-play, Outdoor Wall Boxes supports all cable scenarios for the outside plant. The OSP platform is designed for the harshest environments, supporting NEMA 4 performance requirements, while providing conduit entry through field-deployed knock-outs on both the rear and bottom of the unit. Additional applications include, fiber demarcations, entrance facilities and security systems (CCTV).

Description

Designed from conception to provide fast and easy fiber jumper routing with ease of access to all circuits, the FieldSmart FDP Outdoor 24 Port Wall Box is craft-friendly, keeping the installer's needs for quick deployment, intuitive use and ease of maintenance as the top priorities. Utilizing the Clearview® Cassette, the boxes easily scale from 12 to 24 ports with the industry standard adapter of choice. Ring cut or mid-span capabilities allow distribution cables to be daisy-chained and for fiber hand-off through the riser, while a swinging bulkhead provides rear-access to cassettes and protects sub-unit slack storage. With lockable doors for added protection and a solid enclosure design to protect fiber terminations from damage, the FieldSmart Fiber Delivery Point (FDP) Wall Box product line provides superior fiber management for outdoor environments.

Features and Benefits

Integrity

- Terminations designed, tested and certified to Telcordia GR-326
- Clearfield® FiberDeep® Guarantee: 0.2 dB insertion loss or less, exceeding industry standards
- Fiber cable certified to GR-20 and GR-409
- Supports all industry standard singlemode and multimode connectors
- 100% performance tested for insertion loss, return loss and final mechanical inspect

Protection

- Designed to comply with NEMA 4 requirements
- Zinc-plated for harsh environment reliability
- Radius protected storage for up to three meters of jacketed fiber or patch cord slack is provided (patch side)
- Internal radius protected storage of up to one meter of 900 µm fiber and three meters of jacketed fiber (splice side)
- Rugged steel construction with locking access doors provides security from tampering or inadvertent damage
- Integrated fiber management protects fiber from micro-bend and macro-bend damage
- Ability to padlock the outside door for increased security

Access

- Ships ready to install with cable clamp kit, locks and miscellaneous accessories
- Multiple entry/exit points for feeder/customer premise cables
- Larger design facilitates ease of access in the environments the product is deployed
- Rear wall knockout for conduit entry
- Accessible using a standard can wrench

Investment

- Scalable to 24 ports of fiber using Clearview® Cassettes loaded with the interface of your choice
- Pre-configured and pre-loaded factory terminated assemblies
- Patch only or patch and splice configurations supported
- Boxes can be configured as a tie box and later converted to patch only or patch and splice, utilizing the Clearview Cassette



